




HBK SERIES LED HIGH BAY LIGHT

www.seekingled.com




170lm/w 500W 60°/ 90°

The XJ-HBK500W series high bay light have an output power of 500 watts and a luminous efficiency of up to 170lm/W. They adopt an efficient heat dissipation structure based on the chimney effect principle, and form an up and down airflow cycle through natural convection to achieve rapid cooling, effectively reduce the risk of light decay, and ensure long-term stable operation. Can provide optical angles of 60 ° and 90 ° which can be flexibly adapted to different floor height requirements. The one-piece die-cast aluminum housing is both lightweight and high-strength, with a protection level of IP65, dustproof and waterproof, suitable for harsh environments such as warehouses and workshops. With optimized heat dissipation and optical design, the lamp is efficient and energy-saving while reducing maintenance costs, making it an ideal choice for industrial lighting.





Product size:




Parameter


Model NO.	Power (W)	Efficacy 160-175lm/w
XJ-HBK500W	300-500W (Power Adjustable)	52500-80000

AC Input :	100-277V 50/60Hz
Brand of LED Driver :	MOSO
Light Source :	2835
CRI Range :	Ra>80
CCT Range :	NW(4000K) CW(5700K)
Light Efficiency :	160-175Lm/W
3 in 1 dimmable:	0-10V / PWM / Resistor
Beam Angle :	60°/ 90°
Housing :	Aluminum Alloy
Surge Protection :	6kV line-line,6kV line-earth
Driver Type:	Constant Current (CC)
Protection Rating:	IP65 & IK08
Category of corrosion:	C3
L80B20@25°C:	>100000H
PF:	≥0.95
THD:	<15%
Power Efficiency:	≥0.9
Certifications:	CE, CB
Warranty :	5 Years
Light body color:	Tiefschwarz (RAL 9005)

✱ Above lumens based on 4000K Ra:80



XJ - HBK 500W



Mounting accessories:




A01



A07


accessories	image	material	dimensions	weight	accessoryuse
Standard	A01	Aluminium	M10	0.05KG	Suspension accessories
Optional	A07	SUS304	Φ5x1000mm	0.6kg	Fall prevention safety chain/ Suspension accessories

Product Packaging :





Model	Qty	N.W.(kg)	G.W.(kg)	Meas(mm)
XJ-HBK500W	1PC/ctn	6.6	7.7	406x406x218

Product Installation Instructions:




1. Install expansion screw hook after opening the hole








Hanging Ring




2: Tighten the Hanging Ring and then tighten the screw.




3. Hang the lamp on the hook to ensure firmness


4. Install anti-fall safety wire rope



5. Turn off the power, arrange the access line and connect it to the corresponding line according to the line mark.




Brown "L"
Green+Yellow "E"
Blue "N"



BLK/WHT "Vaux/12V"
PINK "Dim-"
PUR "Dim+."

* Junction Box(User Provide)
Wiring Terminal(User Provide)



6. Turn on the power to complete the installation

* Note : Please make sure the power off before operation, Installation must be performed by skilled electrician who are familiar with the requirements and proper installation methods of LED luminaire, in order to avoid damage or hazard;The external flexible cable or cord of this luminaire can not be replaced, if the cord is damaged, the luminaire must be destroyed,The light source contained in this luminaire shall only be replaced by a qualified person;